



# SANILOX™

ANILOX ROLL CLEANING SYSTEMS

## The Fastest and Most Efficient Roll Cleaning System on the Market

### ADVANTAGES

- Quick and easy to use
- Increases the life of your rolls
- Innovative and environmentally-safe
- A color touch screen makes it easy to operate and track roll inventory data
- No line-screen limitations
- One year warranty and 90-day money back guarantee
- Dust free!

### CLEANS

- Rolls of any diameter
- Any ink, coating, varnish, or glue chemistry
- Journalled rolls
- Sleeves
- Gravure rolls
- Glue rolls
- Coating rolls
- Adhesive rolls



Simple Touch Screen Interface



### DEEP CLEANING

The Sanilox™ system fractures the media to below six microns when applied at 35 psi. As a result, the media reaches the bottom of the cell which ensures that the entire cell gets cleaned.



### DUST-FREE OPERATION

The Sanilox™ system uses a two-stage HEPA filtering system that delivers dust-free operation throughout the entire cleaning process. One collection point allows for easy disposal and zero mess.



### AUTOMATION

The touch screen interface allows for information to be easily entered and stored for simple recall.



### IN-PRESS AND OFF-PRESS OPTIONS

The Sanilox™ system can be quickly and easily transformed from an in-press to an off-press system. No other machine on the market today offers this flexibility.

## HOW IT WORKS

---

The Sanilox™ media delivery system fractures the media to below six microns when applied at 35 psi. As a result, the media reaches the bottom of the cell which ensures that the entire cell gets cleaned (not just the cell walls). Other in-press cleaning technologies require the use of caustic chemicals or portable lasers which can potentially damage the anilox or be harmful to employees. No additional personal protection or tenting of laser radiation is required. The Sanilox™ system is safe for your cylinders, your people, and the environment.

## FLEXIBLE APPLICATIONS

---



Simple Touch Screen Interface

### Sanilox™ In-Press

*Cleans anilox rolls in-press by attaching the track via magnets to the print deck.*

### Sanilox™ Off-Press

*Cleans anilox rolls off-press by using the Anilox Roll Cart attachment. The operator can start the system, walk away, and return to a clean roll.*

## SYSTEM SPECIFICATIONS

---

### Sanilox™ System

- Footprint: 63" L x 27" W x 65" H
- Weight: 985 lbs
- Air: 80 psi, 3/8" quick connect fitting
- (2) 110 volt / 20 Amp dedicated electrical outlets

### Anilox Roll Cart

- Footprint: 107" L x 32" W x 41" H
- Weight: 560 lbs
- (1) 110 volt electrical outlet